

SAFETY FLOOR VINYL

ASSURANCE Easy clean safety vinyl flooring. Reduce slip & stain...



Specification Guide to supply and install to all floors shown in the finishes schedule or listed in this specification Assurance slip retardant homogenous vinyl flooring having inlaid (patented pending) wear resistant component with total thickness of 2.03mm incorporating an easy clean surface design.

Installation is an important part of a successful floor. All product should be installed in accordance with BS 8203-2001 using good trade practice.

Detailed laying instructions and adhesive recommendations are available upon request. Colour coordinated heat weld rods are available in 50L/m reels.

Maintenance may consist of antiseptic or disinfectant solutions to sanitise where necessary. No sealing or polishing is required. Spray buffing is not recommended or required.

Product Data

Overall thickness (nominal)	2.03mm
Wear Layer (nominal)	2.03mm
Weight	3.1kg/m ²
Roll size	183cm x 28Lm
Wear rating	Commercial extra heavy duty

<u>Fire Rating (AS/ISO 9239.1)</u>	
Critical Radiant Flux	10.8kw/m ²
Smoke Obscuration	264% min

Slip Resistnace (AS 4586)
"A" Wet bare feet ramp test
High "R10" Oil ramp test



Specify to suit the cleaners with Assurance...

NOVAPLAS
ARCHITECTURAL PRODUCTS

GOLFBALL
TECHNOLOGY