

SPECIFICATION TEMPLATE FOR:
TACTILE GROUND SURFACE INDICATORS
TACALERT™ TACTILES

RESILIENT FINISHES

PART 1 - GENERAL

1.1 Scope

Supply and Installation of TACALERT Stainless Steel Tactiles base type: (Dovetail - Texbase, anchor back, strong hold) top type (tiger sides, standard, strong hold) with related accessories and equipment to all areas nominated below and/or on plans.

Including but not limited to:

- a) Tactile Product
- b) Adhesives
- c) Templates

1.2 Related Work

Coordinate and cooperate with the following trades:

- * Floor Finishes
- * Handrail Trade
- * Ceramic Tilers
- * Granolithic Work

1.3 Quality Assurance

Installers are required to be extensively experienced in the relevant aspects and class of work required for this section. Installers must carry a letter of certification by Manufacturers / Agent before being awarded the works.

At a place selected by the Architect, construct a prototype of a complete installation of Tacalert Tactiles. On completion of the prototype and approval of all aspects of the installation, work will remain as installed and become the standard for all remaining work.

Installer must complete and submit to Architect a manufacturers pre-installation check-list.

1.4 References

Comply with applicable Australia Standards

- AS 1884 1985 Floor coverings
- AS /NZS 3661.2 Slip Resistance
- AS 3553 1988 Adhesives
- AS/NZ 1428.4 Tactile Installation

Comply with requirements of relevant local Statutory Authorities

1.5 Submissions

Provide sample of product and data sheets of all materials. Including cleaning and maintenance, warranty, product details and applicable ratings.

Drawings of layout should be approved by qualified access consultant and installed by certified installer of manufacturer.

1.6 Delivery, Handling & Storage

All products are to be delivered in the original packaging of supplier bearing the brand name, colour, thickness and any other relevant data.

All materials are to be stored in a dry secure area away from any hazardous goods and contamination.

Order in sufficient time prior to scheduled requirement; to avoid delays.

1.7 Warranty

Installer shall provide a 12 month warranty covering all aspects of the installation performed by this trade, against defective materials for a period of at least 12 months from the date of installation.

Manufacturer will provide warranty on products.

PART 2 – MATERIAL

2.1 Materials

TACALERT Stainless Steel Tactile stud 35mm diameter with bevelled edges for direct surface installation attaining to R10 slip resistance and luminescent contrast value of 45%.

2.1.1 **Proprietary item:** TACALERT Stainless Steel Tactile from NOVAPLAS ARCHITECTURAL PRODUCTS (Tel: 618 9455 2228)

2.1.2 **Location/ Zones:** Refer Architectural Drawing No. _____
Refer to Schedule of finishes pages _____

2.2 Schedule of Quantities

(Refer to drawings for locations and colours of items)

(Refer to bill of quantities of colours and items)

PART 3 – EXECUTION

3.1 Examination

Inspect the site conditions related Tacalert Tactile installation. Arrange for correction if required. Commencement of installation work on site means total acceptance of conditions.

Arrange closure of area during installation.

3.2 Installation

Provide Tacalert Tactiles to quantity and details required.

Refer to drawings for location of the tactiles.

TACALERT Stainless Steel Tactiles to be installed using masonry drilling and fixing ring method and to the manufacturers written instructions and good trade practice.

3.3 Preparation

TACALERT Stainless Steel Tactiles are to be installed in accordance with AS/NZ 1428.4. Comply with reference standards and manufacturer's recommendations.

3.4 Cleaning & Protection

On completion; ensure all studs are firm and clean.

3.5 Completion

Complete all contracted work in accordance with contract documents and written variation orders issued by the Architect.

Work will be regarded complete after being inspected and approved.

Specifiers Note: 1. Brackets () show options to choose from.
2. Tacalert™, Texbase and Dovetail products have copyrights and/or patents applied to them.

END OF SECTION