

NOVATRED ENTRANCE MATTING

Recommended Maintenance

Novatred designer entrance matting will add style and class to any entrance for many years, while also protecting your interior floor coverings. To keep your mat looking and performing at its best the following procedures should be used to maintain Novatred Entrance Matting.

Daily

- 1) Sweep along the mat in the direction of the strips with a stiff broom to prevent any large dirt deposits underfoot causing scratching.
- 2) Vacuum to remove dirt from the matting inserts. This must be done to prevent any sand etc cutting the base of the pile.

Vacuuming or sweeping should be done at least once a day, however it is recommended that vacuuming should occur at least twice a week.

Regular Cleaning

Thorough cleaning of the mats is necessary to keep them performing well. Whenever heavy soiling occurs due to increased traffic or adverse weather, or stubborn stains appear the mats should be removed and cleaned with a neutral detergent and light water pressure.

Maintain the matwell – Bi-monthly the mats should be removed and the matwell vacuumed to remove dirt buildup. The matwell should also be allowed to dry if any moisture is present.

Carefully inspect the matwell for any damage. A damaged matwell will damage the mat. Ensure when mat is put back in place that there is no trip hazard on any edge. Ensure mat is lying flat in the matwell.



P + 61 8 9455 2228**F** + 61 8 9455 2227**W** www.novaproducts.com.au**HQ** 17 Catalano Rd, Canning Vale WA 6155**A** PO Box 1432, Canning Vale WA 6970CLADDING & LINEAR CEILINGS
DOOR & WALL PROTECTION
FLOORING, MATTING TACTILES,
STAIRNOSING & MORE...

Spot Cleaning

Avoid the accumulation of deposits. Inspect the mats regularly and remove any large sediment that could stain the mat over time. Gum deposits for example can be removed using a gum removing solution, and any spot stains can be removed with Schutz ELATEX cleaner (available from Nova Products Global).

Damage

If damage occurs due to wear or loosening of any parts, please contact Novaplas within the day for advice or repair.

By using the above procedures, you will receive many years of performance and good appearance from your Novatred matting.

This information is based on our experience to date and the results of careful testing. However, varying site conditions and methods of use influences practical application of the products. Their success is also dependent upon the professional judgment of the user and his/her conformity to proper trade practice, which are factors outside our control. The issue of this product information invalidates all previous information relevant to this product.

