

Anchorback 2810 Warning Tactile



FEATURES

- Marine Grade 316 stainless steel
- 20mm stemback

Designed for compliance with AS 1428.4

Designed for compliance with AS 1884 1985 Floor coverings

Designed for compliance with AS/NZ 1428.4 Tactile Installation

Backed by extensive warranty

SLIP RESISTANCE PROPERTIES

Slip Rating / Resistance P5

Designed for compliance with AS /NZS 3661.2 Slip Resistance

LUMINENCE PROPERTIES

Important information: To determine a luminance contrast between a substrate see: AS 1428.4:2009.

Luminance Value Approximate value 38

Colour Range

Black and silver available

TYPE Stainless Steel TGS1

RANGE SSTT

DESIGN Anchorback

MATERIAL Stainless Steel

DIMENSIONS SIDE DIA 35mm TOP DIA: 25mm
THICKNESS: 4-5mm

Fire Test

Stainless steel is non-combustible and suited to all parts of 9a ,9c buildings and the like. Tactiles are deemed "Insignificant area therefore not increasing the hazard of fire ".

Abrasion

N/A

Impact Resistance

N/A

Environmental

N/A

Chemical Resistance

N/A

Warranty

12 month installation warranty

Maintenance

Clean with Neutral Detergents, ensure minimal detergent used so as it does not leave residue. Best results clean with Emulsion free Disinfectant (Contact Novaproducts)