

Ecotac Tactiles Studs



FEATURES

- Lightweight
- Stainless Steel
- Includes Screws/Plugs

SLIP RESISTANCE PROPERTIES

Slip rating / Resistance: P4
 Pendulum Mean BPN (4S rubber): 48

LUMINANCE PROPERTIES

Important: To determine a luminance contrast between a substrate see: AS 1428.4.

TYPE Warning Individual Stud

RANGE Hollow Hazard

DESIGN Ecotac

MATERIAL Stainless Steel

DIMENSIONS 35mm diameter x 4.5mm
 Stud height: 5mm

REFERENCE CODE

TT0051J

WARRANTY

12-month installation warranty.

MAINTENANCE

See cleaning and maintenance instructions on page 2.

RECOMMENDED CLEANING & MAINTENANCE

The Tactile Studs as supplied by Novaproducts Global is made from stainless steel, thus they should be cleaned with a mild neutral detergent on a damp cloth. Please ensure the detergent is compatible with the surrounding floor surface. Avoid sealers and harsh cleaners as this will alter the slip resistant properties of the studs. Avoid mechanical cleaning, as this may disrupt the bond to the substrate and void warranties.

Clean with neutral detergents, ensure minimal detergent used, so as it does not leave residue. For best results, clean with emulsion free disinfectant (Contact Novaproducts).

Disclaimer: this information is based on our experience to date and the results of careful testing. However, varying site conditions and methods of use influences practical application of the products. Their success is also dependent upon the professional judgment of the user and his/her conformity to proper trade practice, which are factors outside our control. The issue of this product information invalidates all previous information relevant to this product.